

L-Series Pre-Filter


 L-Series retain the features of M-Series



- Incorporated the third-generation patented cylinder pressure regulation technology, innovational design, automatically regulate the water pressure within 4 bars, ensure the appliances after pre-filter work within safe pressure value.
- Double acting cylinder pressure control, wider range of pressure regulation, more accurate control.
- Pressure control parts are brass forged, durable performance has been improved by more than 10 times compared with traditional diaphragm parts.



- Intelligent touch screen control module, automatic self-cleaning flush, interval days and duration of flushing can be manually set as needed, nanny-style cleaning service.
- The module has low power consumption and can work well with a battery or from a direct power source which is good for many different conditions.
- Control module designed with valve open&close self-inspection function, automatic error alarm, completely eliminate the risk of leakage, modular design for convenient after-sales service.
- Dual pressure gauge shows the inlet pressure and steady pressure after adjustment.



Model	Rated Flow Rate	Filter Mesh	Operating Pressure	Connection Thread	Ambient Temperature	Water Supply	Carton Dimension	Gross Weight
CPF-3-L	3 m ³ /h	40 μm	0.1MPa~1MPa	3/4" Female & Male	5°C~40°C	Municipal	346×183×123(mm)	2.4Kg
CPF-4-L	4 m ³ /h			1"Female & Male			446×210×131(mm)	2.6Kg
CPF-8-L	8 m ³ /h			1" Female & Male 1.25" Female & Male			490×255×156(mm)	4.3Kg